

ROMAN BLIND SYSTEM (RBS) INSTALL INSTRUCTIONS

BY SIMPLY FOLLOWING THESE STEP-BY-STEP INSTRUCTIONS, YOU WILL SOON BE ENJOYING YOUR NEW DRAPERY HARDWARE.

Getting Started:

Please read through all instructions carefully before you begin installation.

Unpack all materials making sure all components are included:

- Assembled RBS rail
- Mounting brackets
- Tension pulley
- Counterweight, optional

Please note that your brackets must be securely attached to the mounting surface. If your screws do not hit wood studs you'll have to use a different fastener, which can be found at any local hardware store.

Tools You Will Need:

- Drill with a 1/8" bit and a Phillips bit
- Phillips screwdriver
- Metal tape measure

Installing Your Roman Blind System:

You are now ready to install your blind hardware.

Wall Mount:

- 1. Measure**
Rails are pre-cut to your specified size.
- 2. Mark**
Mark the height you would like the top of blind rail to be installed.
- 3. Attach Bracket**
Attach your brackets to your desired area. Drill screws through holes for a secure mount.
- 4. Attach Track**
If using Klick bracket, insert track into bracket applying pressure until it "clicks" into place. If using swivel bracket, insert track onto bracket and turn swivel to lock in place.
- 5. Attach Tension Pulley**
First attach the backplate to the wall on the control/chain side of your RBS System. Then wrap cord around pulley and adjust so that chain is tight. Snap cover in place.
- 6. Optional Counterweight**
Slide counterweight into bottom hem pocket.

Ceiling Mount:

- 1. Measure**
Rails are pre-assembled to your specified size.
- 2. Attach Bracket**
Attach bracket to ceiling by first pre-drilling holes for screw diameter when mounting into a ceiling stud. Otherwise, pre-drill and install anchors first before fastening with screws.
- 3. Attach Track**
If using Klick bracket, insert track into bracket applying pressure until it "clicks" into place. If using swivel bracket, insert track onto bracket and turn swivel to lock in place.
- 4. Attach Tension Pulley**
First attach the backplate to the wall on the control/chain side of your RBS System. Then wrap cord around pulley and adjust so that chain is tight. Snap cover in place.
- 5. Optional Counterweight**
Slide counterweight into bottom hem pocket.