SHUTTLE® MOTOR COMPARISON CHART

SHUTTLE® MOTOR COMPARISON CHART



SHUTTLE[®] HD (M) SHUTTLE[®] ECO (S)

SHUTTLE[®] L

A	
/OLTAGE SHUTTLE	14.8V DC
RECEIVER	Internal
BATTERY	Lithium iOn battery + (3-4 months between
MAX POWER	30W
FORQUE	1.0 Nm
TRAVEL SPEED	5.5" per second stand
NOISE LEVEL	< 40 dB(A)
MAXIMUM WEIGHT	55 lbs per motor 40 lbs per motor - cur
DIMENSIONS	2" x 3" x 12.25"
CERTIFICATIONS/MARKINGS	CE/FCC/DOE
COLOR OPTIONS	White
FOUCH CONTROL TECHNOLOGY	\checkmark
NTEGRATED EMERGENCY CONTROL	\checkmark
RF COMMUNICATION STANDARD	\checkmark
Z-WAVE COMMUNICATION	/
AUTOMATION SYSTEM COMPATIBLE	√ using RS485 & dry o
NI-FI COMPATIBLE	\checkmark
WORKS WITH DS-XL LED DIMMER	√ /
WORKS WITH WIRELESS CONNECTOR	\checkmark
CAN BE USED WITH CURVED TRACK	\checkmark
PLUG & PLAY	\checkmark
	10 1/2

WARRANTY


FEATURES

SPECIFICATIONS

VOLTAGE SHUTTLE

RECEIVE

RECEIVER	Internal, optic
POWER SUPPLY	External, 100- 50-60Hz; Ou
MAX POWER	65W
TORQUE	1.5 Nm
TRAVEL SPEED	5.5" per secon 7" per second
NOISE LEVEL	< 40 dB(A)
MAXIMUM WEIGHT	160 lbs per m 120 lbs per m
DIMENSIONS	2.76" x 1.97"
CERTIFICATIONS/MARKINGS	CE/FCC/DOE
COLOR OPTIONS	White / Black
TOUCH CONTROL TECHNOLOGY	\checkmark
INTEGRATED EMERGENCY CONTROL	V
RF COMMUNICATION STANDARD	V
Z-WAVE COMMUNICATION	- \ \
AUTOMATION SYSTEM COMPATIBLE	√ using RS485
WI-FI COMPATIBLE	V
WORKS WITH DS-XL LED DIMMER	V
WORKS WITH WIRELESS CONNECTOR	\checkmark
CAN BE USED WITH CURVED TRACK	\checkmark
PLUG & PLAY	\checkmark
WARRANTY	10 Years





24V DC Internal External, 100-240V AC - 0.8A, 50-60Hz; Output 24V DC - 2.5A 40W

1.0 Nm 5.5" per second standard 7" per second maximum < 40 dB(A) 100 lbs per motor 90 lbs per motor - curved track 2.76" x 1.97" x 7.5"

CE/FCC/DOE White

√ using RS485 & dry contacts

10 Years

100-240V, 50-60Hz 0.8A Internal Internal 40W 1.0 Nm 5.5" per second standard 7" per second maximum < 40 dB(A) 100 lbs per motor

90 lbs per motor - curved track 2.76" x 1.97" x 11" CE/FCC/DOE White

√ using RS485 & dry contacts

10 Years

SPECIFICATIONS FEATURES

SHUTTLE® iOn



- charger n charges)

dard

rved track

contacts

Our wide variety of control options make finding a fit for your windows easy - controlling the drapes by hand, wall switch, remote or even by home automation system. Controlling the motorized system with your smart phone or tablet, you can create and schedule customized room scenes that allow your drapes to operate on their own throughout the day no matter where you are.



TOUCH CONTROL

Open or close your drapes with a gentle tug.

FOREST WALL SWITCH

2-channel wall switch, wireless. Can be used with all Forest Shuttle motors.

FOREST DIAMOND SENSE REMOTE

15-channel remote controls up to 15 motors individually and together, with a timer or manually. Range up to 98 feet. Wall mounted holder included

FOREST WIRELESS CONNECTOR

With the Wireless Connector make your new or existing Shuttle motorized drapery system "smart" Add a smart plug and use with Apple Homekit, Google Assistant, or Amazon Alexa.


FOR ADDITIONAL CONTROL OPTIONS, SEE THE **ROADMAP ON THE FOLLWING PAGES**

2 years on battery pack

10 Years on motor

FOREST MOTOR CONTROLS ROADMAP

FOREST MOTOR CONTROLS ROADMAP



FOREST[°]

* Somfy smart plugs are not available from Forest.

tem	
Data cable clos YI	ES
out feedback	With feedback
ontinuos Voltage + le. Potential free	110 Volt Continuos Voltage + data cable. RS232/RS 485
e M L L iOn nd Sense Remote witch ongle ss Connector smart plug olug third party al RF Multi receiver plug htrol Set	 Shuttle S M L L iOn Diamond Sense Remote Wall Switch WiFi dongle Wireless Connector Forest smart plug Smart plug third party External RF Multi receiver R J 45 plug AC Control Set



DECIDE HOW TO CONTROL YOUR DRAPES IN JUST A FEW STEPS

* Somfy smart plugs are not available from Forest.

