


0

# **DRESDEN MOTORIZED System**

DRESDEN 1 1/8" Motorized Sets FOREST SHUTTLE Motor Specifications FOREST Motor Controls Roadmap

THE WORLD BEHIND YOUR DRAPERIES

# FOREST DRESDEN MOTORIZED SYSTEM





Scan for more information on FOREST DRESDEN MOTORIZED

### DRESDEN FINISHES XX = finish color



## DRESDEN 1 1/8" MOTORIZED

- 1 1/8" motorized system best suited for light to medium weight draperies.
- Rail can be bent or curved. An actual size template is required. Polished chrome cannot be bent or curved.
- Wall or ceiling mount. See bracket count below.

0-5' = 2 brackets	11-15' = 4 brackets
6-10' = 3 brackets	16-20' = 5 brackets

- Motorize with any Forest Shuttle. See all motor specifications on the following pages. All Forest Shuttle motors include a 10 year warranty.
- Control drapes with a gentle tug, wall switch, remote, any home automation system or by smart phone app. See control options on the following pages.

### ASSEMBLED SYSTEM

Includes rail, motor, power supply, motor pulley, return pulley, single wall brackets, carriers, masters, and Diamond remote or wall switch. Finials are optional and should be ordered separately.

See all motor specifications on the following pages.

### **DRESDEN MOTORIZED FINIALS - OPTIONAL**



B124028-XX End Cap Finial





Pescara Finial



**B660-22, 24, 29, 70** Roma Finial



**B3362-XX** Alassio Finial



B3389-100 Ardea Finial B3389/1-XX Socket for Ardea Finial




**B650-22, 29, 59** Verona Finial

# FOREST DRESDEN MOTORIZED SYSTEM

Z			Z		
DRESDEN		COMPONENT	DRESDEN		COMPONENT
•		<b>B809-28-XX</b> 1 1/8″ Aluminum Rail 19' 7″	•	2 1/2"	B11672-220-XX Double Bracket
•	4 1/4"	B899-4-00 Rail Connector	•		B11670-V-XX Adjustable Wall Bracket
•		B11679-L-XX B11679-R-XX Forest Shuttle Motor Pulley	•	<sup>⊥</sup> → 3 <sup>5</sup> / <sub>8</sub> - 5 <sup><i>u</i></sup> → 1 <sup>7</sup> / <sub>8<sup><i>u</i></sup> → 1<sup>1</sup>/<sub>16<sup><i>u</i></sup></sub></sub>	<b>B11873-50-XX</b> Ceiling Bracket
•	43/4	B11699-L-XX B11699-R-XX Somfy Motor Pulley Must purchase motor separately	•	⊥ +5/6"-1	<b>B11873-15-XX</b> Ceiling Bracket 5/8" Projection
•		<b>B11669-L-XX</b> <b>B11669-R-XX</b> Lutron Motor Pulley Must purchase motor separately	•	⊢9//6" → <sup>7</sup> /4" ↓ ⊢ 13/4" →	<b>53408-22,24,29,59</b> Flush Ceiling Bracket Cannot use finials with this bracket
•	43/4	B21679-L-22,29,59 B21679-R-22,29,59 Rollease Versa/Coulisse Motion Blinds Motor Pulley, offset	•		Two Piece Connected Snap Carrier w/ Square Base, in plastic sleeve. Use 1 1/4" snap tape <b>2114-25, 59</b> black 60% fullness, 2 5/8" OC
•	1314 1237.	B21779-L-22,29,59 B21779-R-22,29,59 Rollease Versa/Coulisse Motion Blinds Motor Pulley, in-line			2111-25, 65 brown, 90 grey 80% fullness, 2 3/8" OC 2112-25, 59 black 100% fullness, 2 1/8" OC 2115-25, 59 black
•	4 3/4"	B11683-L-XX B11683-R-XX Standard Return Pulley	•		120% fullness, 1 7/8" OC 52008-25 Slim Line Klick Carrier Draperies hang to conceal track
•	-11:8-1	<b>B11683-41-XX</b> Short Return Pulley for one-way draw	•		<b>52009-25</b> Ball Bearing Carrier for motorization
•		B122028-XX Inside Mount Bracket	•		<b>52508-25</b> Overlap R <b>52509-25</b> Underlap L Belt Master Carrier
•	taaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaa	<b>9012-25</b> Transport Belt Kevlar reinforced	•		<b>52508-25A</b> Overlap R <b>52509-25A</b> Underlap L Belt Master Carrier with snaps
•		<b>52512-25</b> white <b>59</b> black +10% Transport Belt Connector	•		<b>52410-25</b> Butt Right <b>52409-25</b> Butt Left <b>59</b> black +10% Butt Master Carrier with snaps
•	1 <sup>7</sup> /8"	<b>B11670-120-XX</b> Single Bracket	•		<b>2552-25</b> 6″ Extension Arm for master Use w/ two one-way draw


### WWW.FORESTDH.COM 678-721-0004 / SALES@FORESTDH.COM

### FOREST DRESDEN MOTORIZED SYSTEM





# SHUTTLE® MOTOR COMPARISON CHART



### SHUTTLE® HD (M)



### SHUTTLE<sup>®</sup> ECO (S)



### 24V DC

Internal External, 100-240V AC - 0.8A, 50-60Hz; Output 24V DC - 2.5A

40W

1.0 Nm

5.5" per second standard 7" per second maximum

< 40 dB(A)

100 lbs per motor 90 lbs per motor - curved track

2.76" x 1.97" x 7.5"

CE/FCC/DOE

White

√ using RS485 & dry contacts 10 Years

# **SPECIFICATIONS**

# FEATURES

TOUCH CONTROL TECHNOLOGY INTEGRATED EMERGENCY CONTROL **RF COMMUNICATION STANDARD Z-WAVE COMMUNICATION** AUTOMATION SYSTEM COMPATIBLE WI-FI COMPATIBLE WORKS WITH DS-XL LED DIMMER WORKS WITH WIRELESS CONNECTOR CAN BE USED WITH CURVED TRACK PLUG & PLAY WARRANTY

### 24V DC

Internal, optional External, 100-240V AC - 1.5A, 50-60Hz; Output 24V DC - 2.7A

### 65W

1.5 Nm

5.5" per second standard 7" per second maximum

< 40 dB(A)

160 lbs per motor 120 lbs per motor - curved track 2.76" x 1.97" x 9.5"

CE/FCC/DOE

White / Black

√ using RS485 & dry contacts

10 Years

**VOLTAGE SHUTTLE** 

POWER SUPPLY

MAX POWER

TRAVEL SPEED

NOISE LEVEL

DIMENSIONS

COLOR OPTIONS

MAXIMUM WEIGHT

CERTIFICATIONS/MARKINGS

TORQUE

RECEIVER

# **SHUTTLE® MOTOR COMPARISON CHART**



### SHUTTLE® iOn



14.8V DC Internal Lithium iOn battery + charger (3-4 months between charges) 30W

> 1.0 Nm 5.5" per second standard

< 40 dB(A) 55 lbs per motor 40 lbs per motor - curved track 2" x 3" x 12.25" CE/FCC/DOE White

1

 $\sqrt{}$ 

√ using RS485 & dry contacts

- $\sqrt{}$
- $\sqrt{}$
- $\sqrt{}$ V

10 Years on motor 2 years on battery pack Our wide variety of control options make finding a fit for your windows easy - controlling the drapes by hand, wall switch, remote or even by home automation system.





### FOREST REMOTE CONTROLS

We offer two types of RF remote controls: the EasyTouch and the Diamond Sense.

- The EasyTouch controls up to 6 systems, with the option to deactivate unused channels.
- The Diamond Sense is a 15- or 2-channel remote with an LED display. Systems can be operated manually or with the integrated timer.

Both remores have a range of up to 98 feet.

### BOND BRIDGE PRO

With the Bond Bridge Pro, easily pair your Forest remote and get app control for Forest motorized window coverings and other devices all in one place.

### SIDEKICK GEN 3 REMOTE

5- or 1-channel remote control. Pairs directly with drapery motor. Use with Bond Bridge Pro or without. Estimated 10-year battery life.

FEATURES

BATTERY MAX POWER TORQUE TRAVEL SPEED NOISE LEVEL MAXIMUM WEIGHT DIMENSIONS CERTIFICATIONS/MARKINGS COLOR OPTIONS

VOLTAGE SHUTTLE

RECEIVER

TOUCH CONTROL TECHNOLOGY INTEGRATED EMERGENCY CONTROL **RF COMMUNICATION STANDARD Z-WAVE COMMUNICATION** AUTOMATION SYSTEM COMPATIBLE WI-FI COMPATIBLE WORKS WITH DS-XL LED DIMMER WORKS WITH WIRELESS CONNECTOR CAN BE USED WITH CURVED TRACK PLUG & PLAY

WARRANTY



FOR ADDITIONAL CONTROL OPTIONS, SEE THE **ROADMAP ON THE FOLLOWING PAGES.** 










# FOREST MOTOR CONTROLS ROADMAP

### HOW DO YOU WANT TO CONTROL YOUR DRAPERY?



# FOREST MOTOR CONTROLS ROADMAP

